




## 808nm 9W Laser Diode Module

R808±10–9WD–14HHL–PTFS





### Feature

- Output power: 9W
- Wavelength: 808±10nm
- Fiber core: 400 µm, 0.22NA
- Aiming beam: 650nm

### Application

- Medical use
- Material processing

## 808nm 9W Characteristics (25°C)





## Typical Device Performance(25°C)

| Parameter   |                                 | Symbol            | Typical Value          |  | Unit       |
|-------------|---------------------------------|-------------------|------------------------|--|------------|
|             |                                 |                   | R808±10-9WD-14HHL-PTFS |  |            |
| Optical     | CW Output Power                 | P <sub>op</sub>   | 9                      |  | W          |
|             | Center Wavelength               | λ <sub>c</sub>    | 808±10                 |  | nm         |
|             | Spectral Width                  | Δλ                | <6                     |  | nm         |
|             | Temperature drift of wavelength | Δλ /ΔT            | 0.3                    |  | nm/°C      |
| Aiming Beam | Output Power                    | P <sub>a</sub>    | 2                      |  | mW         |
|             | Wavelength                      | λ <sub>a</sub>    | 650±10                 |  | nm         |
|             | Voltage                         | V <sub>a</sub>    | 2.2,5.0                |  | V          |
| Electrical  | Threshold Current               | I <sub>th</sub>   | 1.68                   |  | A          |
|             | Operating Current               | I <sub>op</sub>   | 10.46                  |  | A          |
|             | Operating Voltage               | V <sub>op</sub>   | 2.28                   |  | V          |
|             | Slope Efficiency                | η <sub>es</sub>   | 1.03                   |  | W/A        |
|             | PD Current                      | I <sub>PD</sub>   | <3000                  |  | μA         |
|             | Thermistor                      | R <sub>t</sub>    | 10±5%/3450             |  | kΩ/β(25°C) |
|             | TEC Max Current                 | I <sub>tmax</sub> | 6.0                    |  | A          |
|             | TEC Max Voltage                 | V <sub>tmax</sub> | 9.8                    |  | V          |
| Fiber       | Fiber Core Diameter             | d <sub>core</sub> | 400                    |  | μm         |
|             | Connector                       | -                 | SMA905                 |  | -          |

## Other Parameters

| Parameter | Operating Temperature /°C | Operating Relative Humidity /% | Storage Temperature /°C | Storage Relative Humidity /% | Lead Soldering Temperature(max/°C) |
|-----------|---------------------------|--------------------------------|-------------------------|------------------------------|------------------------------------|
| Min       | 10                        | -                              | -20                     | -                            | -                                  |
| Max       | 30                        | 75                             | 80                      | 70                           | 250(10Sec.)                        |

## Package Dimensions (mm)

| Pin | Function   | Pin | Function                  |
|-----|------------|-----|---------------------------|
| 1   | Case       | 8   | TEC(-)                    |
| 2   | Laser(+)   | 9   | FCD PD(P)                 |
| 3   | Thermistor | 10  | FCD LED(-)                |
| 4   | Thermistor | 11  | FCD LED(+);FCD PD(N)      |
| 5   | Laser(-)   | 12  | Aiming Beam LD(+);[DC 5V] |
| 6   | PD(P)      | 13  | Aiming Beam LD(-);[GND]   |
| 7   | PD(N)      | 14  | TEC(+)                    |

