

Large Aperture Attenuator

Typical Items

Wavelength, nm	Bandwidth, nm	Configuration	Optimization	Attenuation range* (T_{\min} - T_{\max}) @ CWL	Product ID
515	±5	$\lambda/2$ ZO waveplate + 2x TFP	Reflection	0.3-99%	LAT-R-0515
		$\lambda/2$ ZO waveplate + TFP	Transmission	0.5-95%	LAT-T-0515
532	±5	$\lambda/2$ ZO waveplate + 2x TFP	Reflection	0.3-99%	LAT-R-0532
		$\lambda/2$ ZO waveplate + TFP	Transmission	0.5-95%	LAT-T-0532
800	±50	$\lambda/2$ Achromatic waveplate + 2x Broadband (Ultrafast) TFP	Reflection Contrast	0.1-70%	LATU-R2-0800
		$\lambda/2$ Achromatic waveplate + 2x Broadband (Ultrafast) TFP	Reflection	4-96%	LATU-R1-0800
1030	±10	$\lambda/2$ ZO waveplate + 2x Broadband TFP	Reflection	0.3-99%	LAT-R-1030
		$\lambda/2$ ZO waveplate + Broadband TFP	Transmission	0.5-95%	LAT-T-1030
1064	±5	$\lambda/2$ ZO waveplate + 2x TFP	Reflection	0.3-99%	LAT-R-1064
		$\lambda/2$ ZO waveplate + TFP	Transmission	0.5-95%	LAT-T-1064