


# WinCamD-IR-BB

## High resolution beam profiling in the MWIR and FIR spectrum (2-16 μm)

The WinCamD-IR-BB is an imaging solution for lasers in the MWIR and FIR range. With 17 μm pixels, a wavelength range of 2-16 μm, and an integrated shutter, the WinCamD-IR-BB offers unparalleled beam profiling capabilities. With a signal-to-noise ratio that exceeds 1000:1, the WinCamD-IR-BB can make ISO11146 compliant beam measurements. The microbolometer-based camera features very high sensitivity, and the integrated shutter allows for fully automated non-uniformity correction.



The WinCamD-IR-BB is supported by DataRay's full-featured, highly customizable, user-centric software which has no license fees, unlimited installations, and free software updates. The software supports  $M^2$  measurements using our M2DU stages.

For higher power lasers, DataRay offers a range of sampling, absorbing, and reflecting attenuators for use with beam powers exceeding the camera's maximum power limits. Contact [support@dataray.com](mailto:support@dataray.com) for further information.

### System Features

- 2-16 μm wavelength range microbolometer
- 640 x 480, 17 μm pixels
- 10.8 x 8.2 mm active area
- Low irradiance capability: ~75 μW/cm<sup>2</sup> at 5 x peak-to-peak noise
- 30 FPS (7.5 FPS for export)
- Port-powered USB 3.0; no power brick required
- No chopper/TEC
- Integrated shutter allowing for
  - **HyperCal™** – Dynamic Noise and Baseline Correction software
  - **Automated non-uniformity correction (NUC)**
- ≥1000:1 Signal to RMS Noise
- 14-bit ADC
- 14 ms thermal time constant
  - Measure pulsed lasers with PRR ≥ 1 kHz
- Parallel capture on multiple cameras
- Beam propagation analysis
  - ISO 11146  $M^2$  option
  - Beam divergence measurements
  - Focus finding

